

## PD-FLAT 360i/8 ROUND WHITE

### Item number

EP10427930

### GTIN

4015120427930

Ø 8 m	360°	ON/OFF	IP20	1 CH 
-------	------	--------	------	--



### Technical data

#### GENERAL

Device category	Ceiling-mounted presence detector
Product information	Please note the Explanation of circuit breaker in the download area of the product!
Included in delivery	Includes lens mask
User interface	IR remote control with "blue mode" technology
Remote controllable	✓
Conformity	CE, EAC, RoHS, WEEE
Product-specific information	Configuration via ESY-app (ESY-Pen required!) or IR remote control possible.
Warranty	5 years

#### ATTACHMENT

Installation type	Flush-mounted/Device socket Ø 68 mm
Installation position	Ceiling
Installation dimension	Installation depth: 24 mm, Ø 60 mm
Type of connection	Push terminal
Connectable wire cross section	1.5 - 2.5 mm <sup>2</sup>

#### HOUSING

Dimensions	Height 30 mm, Ø 94 mm
Weight	84 g
Material	UV-stabilised polycarbonate
Protection type	IP20
Permissible ambient temperature	-25 °C... +50 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9010

#### ELECTRICAL VERSION

Control system	ON/OFF
----------------	--------

### Product description

- Design presence detector, approx. range 8 m in Ø
- 1 channel, switching, with zero-cross switching, optimised for LED lights
- Master/slave (parallel wiring)
- Low profile design with plastic design covers: round, white - variably interchangeable (alternative: glass, square, black)

### Offers special product features like:

- Zero-cross switching
- Simple parameterisation, remote control and documentation with ESY-Pen and ESY-App

Protection class	II
Nominal voltage	230 V ~ / 50 Hz
In-rush current	78 A / 5 µs
Power consumption	0.3 W

#### SENSORS

Detection angle	360°
Detection range diagonally	Ø 8 m
Detection range head-on	Ø 6 m
Detection range presence	Ø 4 m
Field of detection	up to 50 m <sup>2</sup>
Recommended installation height	2.5 m
Max. mounting height	5 m
Light measurement	mixed light
Level of brightness	5 - 2000 lx

#### CHANNELS (LIGHTING / HVAC)

Number of light channels	1
Push button input lighting	1
Push button input HVAC	-
Number of parallel switchable detectors	10
Slave input	-
Mode	Semi-automatic, Fully automatic
Switching delay from "dark to light"	300 s
Switching delay from "light to dark"	30 s
Constant light control	-
Channel	C1 Lighting
Function	Switching
Switching capacity	230 V/50 Hz

## PD-FLAT 360i/8 ROUND WHITE

Item number	GTIN		
EP10427930	4015120427930	2300 W/10 A (cos phi = 1) 1150 VA/5 A (cos phi = 0,5) 600 W LED	Push button input ✓
Switch contact	make contact / non-floating		Impulse mode ✓
			Switch-off delay time 60 s...30 min (adjustable in steps)

### Factory settings

GENERAL		Operating mode	
Sensitivity	100 %	Level of brightness/switching threshold	fully automatic
		Switch-off delay time	100 lx
			5 min

  

CHANNELS (LIGHTING / HVAC)	
Channel	C1 Lighting

### Accessories

Product designation	Item number	Product description	GTIN
<b>Cover</b>			
FLAT COVER ROUND WH	EP00007231	Cover for FLAT series, round, white	4015120007231
FLAT COVER ROUND BK	EP00007279	Cover for FLAT series, round, black	4015120007279
FLAT COVER LARGE ROUND WH	EP10428579	Cover for FLAT series, Ø104 mm, round, white	4015120428579
FLAT COVER LARGE ROUND BK	EP10428098	Cover for FLAT series, Ø104 mm, round, black	4015120428098
FLAT COVER SQUARE WH	EP00007248	Cover for FLAT series, square, white	4015120007248
FLAT COVER SQUARE BK	EP00007286	Cover for FLAT series, square, black	4015120007286
FLAT COVER GLASS ROUND WH	EP00007255	Cover for FLAT series, glass, round, white	4015120007255
FLAT COVER GLASS ROUND BK	EP00007293	Cover for FLAT series, glass, round, black	4015120007293
FLAT COVER GLASS ROUND GY	EP00007323	Cover for FLAT series, glass, round, grey	4015120007323
FLAT COVER GLASS SQUARE WH	EP00007262	Cover for FLAT series, glass, square, white	4015120007262
FLAT COVER GLASS SQUARE BK	EP00007309	Cover for FLAT series, glass, square, grey	4015120007309
FLAT LENS MASK	EP00007392	Spare part lens mask for PD-FLAT WH products	4015120007392
<b>Electrical accessories</b>			
FILTER 230 V	EP10426988	Filter for suppression of inductive loads, such as relays, contactors, fluorescent lamps and transformers	4015120426988
<b>Mounting</b>			
FLAT MOUNTING SET IP20 FM	EP10426889	Recessed ceiling mounting set for FLAT series includes installation bracket and dust-protected box	4015120426889
<b>Protection</b>			
BASKET GUARD ROUND LARGE	EM10425608	Basket guard for presence and motion detectors and smoke detectors, Ø 180 mm, height 90 mm	4015120425608
BASKET GUARD ROUND SMALL	EM10425615	Basket guard for presence and motion detectors and smoke detectors, Ø 165 mm, height 70 mm	4015120425615
<b>Remote control</b>			
ESY-Pen	EP10425356	ESY-Pen and ESY-App, two tools for every task: (1) Parameterisation, (2) remote control, (3) light measurement, (4) project management	4015120425356
REMOTE CONTROL MDi/PDi	EM10425509	IR remote control for presence detectors and motion detectors	4015120425509

## PD-FLAT 360i/8 ROUND WHITE

**Item number**      **GTIN**  
 EP10427930      4015120427930

Dimension drawing	Field of detections	Detection range	
		<p>■ Diagonally (A)</p>	<p>Ø 8 m</p>
		<p>■ Frontal (B)</p>	<p>Ø 6 m</p>
		<p>■ Presence area (C)</p>	<p>Ø 4 m</p>

Circuit diagram	Circuit diagram

Standard operation with optional control via a closing button and parallel wiring of max. 8 devices

When connecting inductors (e.g. relays, contactors, ballasts) the use of a filter (RC-Filter) may be necessary.

### Detailed product description

- Design presence detector, approx. range 8 m in Ø
- 1 channel, switching, with zero-cross switching, optimised for LED lights
- Master/slave (parallel wiring)
- Low profile design with plastic design covers: round, white - variably interchangeable (alternative: glass, square, black)
- Flush mounting and ceiling flush mounting
- Switch input