

CU-DIN DIM 4-CH 1.5A KNX

Item number **GTIN**
 EC10430312 4015120430312

Product description

KNX DIN rail module, dimming actuator, 4-way, 1.5-A switching capacity per channel



Technical data

GENERAL

Device category	Actuator
User interface	ETS-Software
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	3 years

ATTACHMENT

Installation type	DIN rail
Installation position	Switching cabinet
Installation dimension	Installation length: 90 mm x Installation width: 216 mm x Installation depth: 65 mm
Type of connection	Push terminal
Connectable wire cross section	0.2 – 6 mm ²

HOUSING

Dimensions	Length 90 mm x Width 216 mm x Height/Depth 65 mm
Weight	757 g

Protection type	IP20
Permissible ambient temperature	-5 °C...+45 °C
Relative humidity	5 – 93 %, non-condensing
Colour	grey

ELECTRICAL VERSION

Control system	KNX
Protection class	II
Nominal voltage	29 – 31 V DC / 60 Hz
Power consumption	0.4 W
Power consumption	15 mA
Stand-by consumption	< 0.4 W


AUTOMATION

Bus voltage	29 - 31 V DC
Number of inputs	0
Power loss	8 W
Rated current	1,5 A
Horizontal pitch (HP)	12

CU-DIN DIM 4-CH 1.5A KNX

Item number **GTIN**
EC10430312 4015120430312

Dimension drawing



Detailed product description

- KNX DIN rail module
- Dimming actuator 4-way with scene control
- Status feedback
- Time functions
- Short-circuit protection
- Status recovery
- Threshold value control
- Overload protection
- Sequence control
- Overheating alarm
- Stairwell light function
- Heating control (PWM)
- Dimming upper limit
- 1.5 dimming curve (extremely soft dimming)
- Flashing
- Dimming lower limit