


SMARTDRIVER x8 TW ELC KNX

Item number **GTIN**
 EC10431050 4015120431050



Product description

- Light control for up to 8 ELC lights (ELC = ESYLUX Light Control) with Tunable White
- Integrated constant lighting control for high energy efficiency
- 2 push button inputs for conventional push buttons (230 V)
- Compatible with selected DALI push buttons and DALI I/O devices
- SymbiLogic technology for biologically effective light
- Manual override and scenes in 2 separate light channels
- Lights are connected via RJ45
- Can be networked with other ELC light controls using DALI
- Integrated KNX module for direct integration into a KNX bus system (no gateway required)

Technical data

GENERAL	
Warranty	5 years
Device category	Control
Product information	ELC lighting systems combine compatible components via plug-and-play: ELC main lighting, control unit and sensor system. Alternatively: The ELC lights are also suitable for plug-and-play installation outside ELC lighting systems if suitable driver sets (accessories) are used
User interface	Push button input, IR remote control, ETS-Software
Remote controllable	✓
Conformity	CE, EAC, RoHS, WEEE
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Ceiling
Type of connection	Push terminal
Connectable wire cross section	1.5 – 2.5 mm ²
HOUSING	
Dimensions	Length 474 mm x Width 345 mm x Height/Depth 140 mm
Weight	4965 g
Material	Steel, galvanised
Protection type	IP20

Permissible ambient temperature	0 °C...+40 °C
Relative humidity	5 – 93 %, non-condensing
Colour	white

ELECTRICAL VERSION

Control system	ELC (ESYLUX Light Control), DALI, KNX
Protection class	I
Nominal voltage	230 V ~ / 60 Hz
Power consumption	260 W
Stand-by consumption	7.5 W

CHANNELS (LIGHTING / HVAC)

Number of light channels	2
Number of control units per group	5
Number of light groups	10
Push button input lighting	2
Number of HVAC-channels	2
Number of scenes	4
Orientation light	disabled/10 – 50 %, 2 values can be selected
Constant light control	✓
Orientation light duration or time	✓
HCL-lighting control	✓
Number of outputs luminaires ELC	8
Number of outputs luminaires DALI	4

Factory settings

SMARTDRIVER x8 TW ELC KNX

Item number	GTIN
EC10431050	4015120431050

GENERAL	
Sensitivity	100 %
SymbiLogic	✓
Afterglow luminous efficiency	10 %
Orientation light ON	–
Orientation light, depending on brightness	✓
Switching threshold for orientation light	500 lx
Deviation (%)	0 %
Luminous efficiency switch-on value	50 %

Colour temperature switch-on value	4000 K
CHANNELS (LIGHTING / HVAC)	
Channel	C1 Lighting
Operating mode	fully automatic
Level of brightness/switching threshold	500 lx
Switch-off delay time	5 min
Luminous efficiency of orientation light	10 %
Duration of switch-off warning	60 s

System components

Product designation	Item number	Product description	GTIN
Cable			
CABLE RJ10 10m WH	EC10431500	Connection cable RJ10, 10 m, white	4015120431500
CABLE RJ10-OPEN END 10m WH	EC10431517	Connection cable RJ10 Open end, 10 m, white	4015120431517
CABLE RJ11 10m WH	EC10431524	Connection cable RJ11, 10 m, white	4015120431524
CABLE RJ45 5m RD	EQ10019890	Connection cable RJ45, 5 m, red	4015120019890
CABLE RJ45 5m BL	EQ10019982	Connection cable RJ45, 5 m, blue	4015120019982
CABLE RJ45 10m BL	EQ10019999	Connection cable RJ45, 10 m, blue	4015120019999
CABLE RJ45 10m RD	EQ10020155	Connection cable RJ45, 10 m, red	4015120020155
CABLE-SET RJ45 5m TW x8	EC10431203	Connection cable set for SMARTDRIVER x8 TW series	4015120431203
CABLE-SET RJ45 10m TW x8	EC10431210	Connection cable set for SMARTDRIVER x8 TW series	4015120431210
Ceiling-mounted presence detector			
PD-C 360i/8 ELC	EP10427602	Presence detector with 360° field of detection for ceiling mounting	4015120427602
PD-C 360i/24 ELC	EP10427619	Presence detector with 360° field of detection for ceiling mounting	4015120427619
PD 360i/8 BASIC ELC	EB10431357	Presence detector for ESYLUX Light Control with 360° field of detection for ceiling mounting	4015120431357
Push button			
PUSH BUTTON x8 TW ELC	EC10430930	DALI 8 x push button Tunable White	4015120430930
PUSH BUTTON x8 CLASSROOM ELC	EC10431241	DALI 8-way push button	4015120431241
PUSH BUTTON x4 PATIENT ROOM ELC	EC10431258	DALI 4-way push button	4015120431258
PUSH BUTTON x8 PATIENT ROOM ELC	EC10431265	DALI 8-way push button	4015120431265
Recessed light			
CELINE-2 PNL 600 DDP OP 3800 8TW IP20 ELC	EQ10132322	LED light with opal cover (diffuser)	4015120132322
CELINE-2 PNL 600 DDP TR 4200 8TW IP20 ELC	EQ10132353	LED light with prismatic cover (diffuser)	4015120132353
CELINE-2 PNL 625 DDP OP 3800 8TW IP20 ELC	EQ10132384	LED light with opal cover (diffuser)	4015120132384
CELINE-2 PNL 625 DDP TR 4200 8TW IP20 ELC	EQ10132414	LED light with prismatic cover (diffuser)	4015120132414


SMARTDRIVER x8 TW ELC KNX

Item number	GTIN
EC10431050	4015120431050

Accessories

Product designation	Item number	Product description	GTIN
Electrical accessories			
ACTUATOR FULL AUTO C3 DALI	EP10427473	Modul for the conversion of bus commands from the DALI presence detector and other light controls into switching signals (fully automatic)	4015120427473
ACTUATOR SEMI AUTO C4 DALI	EP10427480	Modul for the conversion of bus commands from the DALI presence detector and other light controls into switching signals (semi-automatic)	4015120427480

Dimension drawing



Detailed product description

- Light control for up to 8 ELC lights (ELC = ESYLUX Light Control) with Tunable White
- Integrated constant lighting control for high energy efficiency
- 2 push button inputs for conventional push buttons (230 V)
- Compatible with selected DALI push buttons and DALI I/O devices
- SymbiLogic technology for biologically effective light
- Manual override and scenes in 2 separate light channels
- Lights are connected via RJ45
- Can be networked with other ELC light controls using DALI
- Integrated KNX module for direct integration into a KNX bus system (no gateway required)