


DATA SHEET

ALVA UDL TR 13° 1100 840 AN

Item number EL10830020
GTIN 4015120830020



Product description

- High-quality aluminium LED up/down light
- Dirt-repellent thanks to powder coating with lotus effect
- Beam angle: 2 x 13°

Offers special product features like:

- Protected against sea air

Technical data

GENERAL

Device category	Up-/Downlight
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years

ATTACHMENT

Installation type	Surface mounting
Installation position	Wall
Type of connection	Push terminal
Connectable wire cross section	1.50 – 2.50 mm ²
Number of contacts	3

HOUSING

Dimensions	Length 176 mm x Width 100 mm x Height/Depth 160 mm
Weight	1550 g
Material	powder-coated aluminium
Protection type	IP65
Permissible ambient temperature	-25 °C...+40 °C
Impact resistance	IK09
Colour	graphite gray, similar to RAL 7024
Glow wire test in accordance with IEC 60695-2-10	650 °C

ELECTRICAL VERSION

Control system	ON/OFF
----------------	--------

Protection class	I
Nominal voltage	230 - 230 V ~ / 50 Hz
In-rush current	6 A / 369 µs
Leakage current	0.017 mA
Power consumption	70 mA

LIGHT


Diffuser	transparent
Light emission	direct/indirect
Beam angle	13 °
Flicker factor	<10 %
Rated output P	10 W
Luminous flux	1050 lm
Luminous efficacy	105 lm/W
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	2 SDCM
Color Quality Scale	80
L70B10 lifetime at 25 °C	125000 h
Lebensdauer L70B50 bei 25 °C	225000 h
Lebensdauer L80B10 bei 25 °C	80000 h
Life time L80B50 at 25 °C	140000 h
Lebensdauer L90B10 bei 25 °C	40000 h
Life time L90B50 at 25 °C	70000 h

DATA SHEET

ALVA UDL TR 13° 1100 840 AN

Item number **GTIN**
EL10830020 4015120830020

Dimension drawing



Lichtverteilung

