

ELSA-2 DL 225 OP 110° 1800 830 DALI WH

Item number E010298943
GTIN 4015120298943

110 V - 230 V ~	IP20 IP44	LED 3000 K	CRI 80	CQS 80-85
--------------------	--------------	---------------	-----------	--------------



Product description

- LED downlight, 3000K with opal cover (diffuser), 18W, for ceiling mounting without additional accessories
- High light quality and system performance
- Operating device DALI with SwitchDIM, included

Offers special product features like:

- SwitchDIM function

Technical data

GENERAL	
Device category	Downlight
User interface	DALI-Bus
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE, SundaHus
Warranty	5 years
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Ceiling
Installation dimension	Installation depth: 50 mm, Ø 225 mm
Type of connection	Open end
Connectable wire cross section	0.75 – 2.50 mm ²
Number of contacts	3
Length of cable	0.18 m
HOUSING	
Dimensions	Height/Depth 25 mm, Ø 240 mm
Weight	1000 g
Material	powder-coated aluminium
Protection type	IP20 / IP44 below the ceiling (built-in)
Permissible ambient temperature	-20 °C...+40 °C
Relative humidity	5 - 93 %, non-condensing
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C
ELECTRICAL VERSION	
Control system	DALI

Protection class	II
Nominal voltage	220 - 240 V ~ / 50 - 60 Hz
In-rush current	9.1 A / 98 µs
Leakage current	0.009 mA

LIGHT	
Diffuser	opal
Light emission	direct
Beam angle	110 °
Unified Glare Rating	≤ 25
Flicker factor	0 %
Rated output P	19 W
Luminous flux	1700 lm
Luminous efficacy	89 lm/W
Colour temperature	3000 K
Colour rendering index Ra	> 80
Colour tolerance	2 SDCM
Color Quality Scale	>80
L70B10 lifetime at 25 °C	60000 h
Lebensdauer L70B50 bei 25 °C	60000 h
Lebensdauer L80B10 bei 25 °C	40000 h
Life time L80B50 at 25 °C	40000 h
Lebensdauer L90B10 bei 25 °C	20000 h
Life time L90B50 at 25 °C	20000 h
Photobiological safety	RG0

SENSORS	
CHANNELS (LIGHTING / HVAC)	


ELSA-2 DL 225 OP 110° 1800 830 DALI WH

Item number	GTIN
E010298943	4015120298943


Accessories

Product designation	Item number	Product description	GTIN
Adapter			
ELSA-2 RING 225	E010300264	Adapter ring 225–265 mm for ELSA-2 series	4015120300264
Electrical accessories			
JUNCTION BOX 5-POLE BK	E010430947	Universal junction box, black, 5-pin, 2.5 mm ²	4015120430947
Mounting			
ELSA-2 MOUNTING FRAME 225 SM WH	E010300899	Ceiling installation frame for ELSA-2 225 series	4015120300899


Dimension drawing



Light distribution




Circuit diagram



Standard operation

Circuit diagram




Standard operation CB

DATA SHEET

ELSA-2 DL 225 OP 110° 1800 830 DALI WH

Item number **GTIN**
E010298943 4015120298943

Circuit diagram



Standard operation SwitchDIM