

## ELSA-2 DL 225 OP 110° 1800 840 WH

**Item number** E010299018  
**GTIN** 4015120299018

110 V - 230 V ~	IP20 IP44	LED 4000 K	CRI 80	CQS 80-85
--------------------	--------------	---------------	-----------	--------------

### Product description

- LED downlight, 4000K with opal cover (diffuser), 18W, for ceiling mounting without additional accessories
- High light quality and system performance
- Operating device on/off, included



### Technical data

#### GENERAL

Device category	Downlight
Remote controllable	–
Conformity	CE, EAC, RoHS, WEEE
Warranty	5 years

#### ATTACHMENT

Installation type	Recessed mounting
Installation position	Ceiling
Installation dimension	Installation depth: 40 mm, Ø 225 mm
Type of connection	Open end
Connectable wire cross section	0.75 – 2.50 mm <sup>2</sup>
Number of contacts	3
Length of cable	0.18 m

#### HOUSING

Dimensions	Height/Depth 25 mm, Ø 240 mm
Weight	937 g
Material	powder-coated aluminium
Protection type	IP20 / IP44 below the ceiling (built-in)
Permissible ambient temperature	-20 °C...+40 °C
Relative humidity	5 – 93 %, non-condensing
Colour	white, similar to RAL 9003
Glow wire test in accordance with IEC 60695-2-10	650 °C

#### ELECTRICAL VERSION

Control system	ON/OFF
Protection class	II
Nominal voltage	220 – 240 V ~ / 50 – 60 Hz

#### LIGHT

Diffuser	opal
Light emission	direct
Beam angle	110 °
Unified Glare Rating	≤ 25
Flicker factor	0 %
Rated output P	18 W
Luminous flux	1800 lm
Luminous efficacy	100 lm/W
Colour temperature	4000 K
Colour rendering index Ra	> 80
Colour tolerance	1 SDCM
Color Quality Scale	>80
L70B10 lifetime at 25 °C	60000 h
Life time L70B50 at 25 °C	60000 h
Life time L80B10 at 25 °C	40000 h
Life time L80B50 at 25 °C	40000 h
Life time L90B10 at 25 °C	20000 h
Life time L90B50 at 25 °C	20000 h
Photobiological safety	RG0


## ELSA-2 DL 225 OP 110° 1800 840 WH

Item number	GTIN
E010299018	4015120299018


### Accessories

Product designation	Item number	Product description	GTIN
<b>Adapter</b>			
ELSA-2 RING 225	E010300264	Adapter ring 225–265 mm for ELSA-2 series	4015120300264
<b>Electrical accessories</b>			
JUNCTION BOX 5-POLE BK	E010430947	Universal junction box, black, 5-pin, 2.5 mm <sup>2</sup>	4015120430947
<b>Mounting</b>			
ELSA-2 MOUNTING FRAME 225 SM WH	E010300899	Ceiling installation frame for ELSA-2 225 series	4015120300899


### Dimension drawing



### Light distribution



### Circuit diagram



Standard operation.

### Detailed product description

- LED downlight, 18 W for ceiling mounting
- Recessed luminaire with opal cover (diffuser)
- High-quality housing, aluminium lamp body, white powder-coated (RAL 9003)
- Can be used for ceiling mounting without additional accessories
- Colour temperature: 4000 K with the lowest colour tolerances
- Luminous flux: 1750 lm

# DATA SHEET



## ELSA-2 DL 225 OP 110° 1800 840 WH

Item number	GTIN
E010299018	4015120299018

- High light quality
- Excellent system efficiency
- Life time L80B50 at 25 °C: 40000 h
- Operating device: on/off (included)