

PUSH BUTTON x2 DALI-2 WH

Item number

EP10431609

GTIN

4015120431609

DALI-2



Product description

- 2-way button to act as certified DALI-2 input device
- Individual function allocation using application controller (DALI-2 control unit)
- Function assignments of buttons can be individually labelled
- Power supply from DALI bus
- Compatible with 55 mm frames from most manufacturers

Technical data

GENERAL	
Device category	Push button
Conformity	CE, RoHS, WEEE, EAC
Warranty	5 years
ATTACHMENT	
Installation type	Recessed mounting
Installation position	Wall
Installation dimension	Installation length: 55.5 mm x Installation width: 55.5 mm x Installation depth: 8 mm
Type of connection	Push terminal
Connectable wire cross section	0.75 – 2.5 mm ²
HOUSING	
Dimensions	Length 71 mm x Width 71 mm x Height/Depth 21.5 mm

Weight	62 g
Material	UV-resistant plastic
Protection type	IP20
Permissible ambient temperature	-20 °C...+50 °C
Relative humidity	max. 80 %, non-condensing
Colour	white


ELECTRICAL VERSION	
Control system	DALI-2
Protection class	III
Nominal voltage	12.5 – 22.5 V DC
No load current DALI	2 mA
Peak current DALI	10 mA

AUTOMATION	
Bus voltage	12 - 22,5 V DC


PUSH BUTTON x2 DALI-2 WH

Item number **GTIN**
EP10431609 4015120431609

Dimension drawing




Circuit diagram



Standard operation.

Circuit diagram



Master/slave connection for presence detectors: a maximum of 8 slave devices may be connected to one master.

Detailed product description

- 2-way button to act as certified DALI-2 input device
- Individual function allocation using application controller (DALI-2 control unit)
- Function assignments of buttons can be individually labelled
- Power supply from DALI bus
- Compatible with 55 mm frames from most manufacturers